



Stratus Arctic 1000

Arctic 1000 is a cold flow promoter designed to maintain the flow properties of Diesel and Biodiesel in engines and tanks during extreme winter conditions.

Stratus Arctic 1000

Arctic 1000 is a cold flow promoter designed to maintain the flow properties of Diesel and Biodiesel in engines and tanks during extreme winter conditions.

It is suitable for use with road fuel (DERV) and Gas Oil with Biofuel contents of up to 50%. Arctic 1000 can extend the minimum temperature at which the fuel can be used without flow problems as follows:

Arctic 1000 Addition Rate	Protected Temperature Range, °C
Standard Winter Diesel	-12 to -14 °C
1 litre of Arctic 1000 per 1,000 litres of fuel	Down to -24 °C
1 litre of Arctic 1000 per 500 litres of fuel	Down to -30 °C

KEY PRODUCT FEATURES

- Should be dosed in tanks prior to addition of fresh fuel to aid mixing.
- Is a preventative maintenance product and cannot reverse the condition of fuel that has already gelled.
- Has no direct impact on engine performance, but it is compatible with other Stratus Energy products such as [MULTIPLANT HD](#), [FUELGUARD](#) and [POWERGEN](#) that improve the properties of Diesel and Biodiesel in a range of applications.

Where Summer grade Diesel is mixed with Winter grade Diesel, the protection offered by Arctic 1000 may be changed – if in doubt, please contact Stratus Energy for technical guidance.



Stratus Energy Limited

Thornhouse Business Centre
30 Ballot Road, Irvine KA12 0HW

Tel: +44 (0)1294 276924

Fax: +44 (0)1294 275119

Email: info@stratusenergy.co.uk

www.stratusenergy.co.uk

Distributed by: